

Smart Mini



Functii



Wallbox cu design solid
Respecta IP65 si IK10 conform testelor de laborator excellent water protection.



Indicator luminos
Afiseaza starea incarcarii in timp real



Smart mini
Teison smart components highly integrated in a 234.4x233.6x147.7 mm Size mini body



TUV certificat
All parts passed CE Certificates, and tested by TUV.



Smart incarcare
The smartphone App can realize the remote control and organize.
Integration with OCPP 1.6 J-SON system.



● Black



● Silver

Specificatii tehnice

Specification			
Model	TS-EVC07-003S	TS-EVC11-003S	TS-EVC22-003S
Proprietati electrice			
Tensiune	230V AC ±10%	400V AC ±10%	400V AC ±10%
Iesire Curent	32A	16A	32A
Frecventa	50/60 Hz	50/60 Hz	50/60 Hz
Putere iesire	7kW	11kW	22kW
Protectie curent rezidual	TYPE A(30mA AC)		
Design			
Iesire incarcare	Type 2 socket		
Material carcasa	PCV0 for outdoor		
Metoda instalare	Wall-mount / Column		
Protocol comunica-re	OCPP 1.6 J-SON		
Standard siguran-ta	EN IEC 61851-21-2:2021; EN IEC 61000-6-1:2019; EN IEC 61000-6-2:2019; EN IEC 61000-6-3:2021; EN IEC 61851-1:2019; EN IEC 61000-6-4:2019; ETSI EN 300 328 V2.2.2:2019; ETSI EN 300 330 V2.1.1:2017; ETSI EN 301 489-1 V2.2.3:2019; ETSI EN 301 489-3 V2.1.1:2019; ETSI EN 301 489-17 V3.2.4:2020; EN IEC 62311:2020, IEC 61851-1:2017		
Garantie	2 years		
Performanta mediu			
Nivel protectie	IP65		
Altitudine opere-re	< 2000M		
Loc utiliza-re	Interior/Exterior		
Temperatura opere-re	-30 C ~+50C		
Umiditate opere-re	5%-95%, No condensation		
Presiune atmosferica	80kPa~101kPa		
Functionality			
Gateway retea	Bluetooth?WIFI and Ethernet implicit		
Aplicatie mobila (Ios and Android supported) functions under Bluetooth	Scheduled incarcare?Start incarcare?Stop incarcare? Reglare curent (memorable)?plug and play incarcare? switch on APP、Charging status shown on APP		
Added APP funtions under WIFI / 4G / Ethernet	Inregistrari incarcare shown on mobile APP?view and update the PIN code?functie actualizare firmware (OTA)?multiple wallbox control		

Configuratie produs

Detalii ambalare			
Dimensiune produs	233.6*234.4*147.7mm	233.6*234.4*147.7mm	233.6*234.4*147.7mm
Greutate produs	4.4KG	5.2KG	5.4KG
OptionalConfig			
Protectie curent rezidual	TYPE B (AC 30MA+DC 6 MA) optional		
Gateway retea	4G optional		
O-PEN detection	optional		
RFID	optional(with 3 RFID cards)		
load balance	RS485 meter/CT-Clamp optional		
Metoda instalare	Coloana		

OptionFuncii rance



Tip priza



montaj pe perete / montaj pe coloana

