

Smart Pro



Type 2



GB/T

Functii



Wallbox cu design solid
Respecta IP65 si IK10 conform testelor de laborator



5 inch hd touch ecran
Easiest user interaction and stare in timp real view



Indicator luminos
Afiseaza starea incarcarii in timp real



Senzor RFID
Solutie de identificare si plata



Access hole
For easiest maintenance



Port etans
Pentru siguranta maxima



Buton de urgenta
Apasare pentru intreruperea imediata a alimentarii



Cablu TPU
Cablu 4,5 m, durabil, rezistent la frig pana la -30?



Conector aprobat TUV
Completed shaped and easy hold ; Silver plated terminals to minimize wear and tear on EV incarcare socket

Specificatii tehnice

Specification			
Model	TS-EVC07-002C-001 TS-EVC07-002C-001S	TS-EVC11-002C-001 TS-EVC11-002C-001S	TS-EVC22-002C-001 TS-EVC22-002C-001S
Proprietati electrice			
Tensiune	230V AC ±10%	400V AC ±10%	400V AC ±10%
Iesire Curent	32A	16A	32A
Frecventa	50/60 Hz	50/60 Hz	50/60 Hz
Putere iesire	7kw	11kw	22kw
Protectie curent rezidual	TypeB (AC 30mA+DC 6mA)		
Design			
Buton oprire urgenta	Da		
Display	5" LCD touch ecran		
RFID Function	Da		
Iesire incarcare	One incarcare socket (Type 2) / One 4.5M incarcare cable		
Cablu alimentare	0.5M		
Material carcasa	PCV0 for outdoor		
Panou frontal	PC		
Metoda instalare	Wall-mount/Column		
Gateway retea	Ethernet?Wifi		
Protocol comunica-re	OCPP 1.6J, suporta upgrade la OCPP 2.0.1		
Standard siguranta	EN IEC 61851-1: 2019; IEC 61851-1:2017; EN IEC 61851-21-2:2021; EN IEC 61000-6-1:2019; EN IEC 61000-6-2:2019; EN IEC 61000-6-3:2021; EN IEC 61000-6-4:2019; ETSI EN 300 328 V2.2.2:2019; ETSI EN 300 330 V2.1.1:2017; ETSI EN 301 489-1 V2.2.3:2019; ETSI EN 301 489-3 V2.1.1:2019; ETSI EN 301 489-17 V3.2.4:2020 ; EN IEC 62311:2020		
Garantie	2 years		
Performanta mediu			
Nivel protectie	IP65		
Altitudine operare	< 2000M		
Loc utiliza-re	Interior/Exterior		
Temperatura operare	-30 C ~ +50 C		
Umiditate operare	5% ~ 95%, No condensation		
Presiune atmosferica	80kPa ~ 101kPa		

Configuratie produs

Detalii ambalare			
Dimensiune produs	398*324*120mm	398*324*120mm	398*324*120mm
Greutate produs	10KG	11KG	12KG
Optional Config			
Dynamic load balancing	RS485 meter or local junction box (optinal)		
Contor energie	MID meter		
Gateway retea	4G		

OptionFuncții



Tip priza



Tip conector



Type2/GBT Optional



Incarcare socket



Cablu length customization



Type 2



GB/T



Wallbox cu design solid

Respecta IP65 si IK10 conform testelor de laborator



5 inch hd touch ecran

Easiest user interaction and stare in timp real view



Indicator luminos

Afiseaza starea incarcarii in timp real



Senzor RFID

Solutie de identificare si plata



Access hole

For easiest maintenance



Port etans

Pentru siguranta maxima



Buton de urgenta

Apasare pentru intreruperea imediata a alimentarii



Cablu TPU

Cablu 4,5 m, durabil, rezistent la frig pana la -30?



Conector aprobat TUV

Completed shaped and easy hold ; Silver plated terminals to minimize wear and tear on EV incarcare socket

Specificatii tehnice

Specification			
Model	TS-EVC07-002C-001 TS-EVC07-002C-001S	TS-EVC11-002C-001 TS-EVC11-002C-001S	TS-EVC22-002C-001 TS-EVC22-002C-001S
Proprietati electrice			
Tensiune	230V AC ±10%	400V AC ±10%	400V AC ±10%
Iesire Curent	32A	16A	32A
Frecventa	50/60 Hz	50/60 Hz	50/60 Hz
Putere iesire	7kw	11kw	22kw
Protectie curent rezidual	TypeB(AC 30mA+DC 6mA)		
Design			
Buton oprire urgenta	Da		
Display	5" LCD touch ecran		
RFID Function	Da		
Iesire incarcare	One incarcare socket (Type 2)/ One 4.5M incarcare cable		
Cablu alimentare	0.5M		
Material carcasa	PCV0 for outdoor		
Panou frontal	PC		
Metoda instalare	Wall-mount/Column		
Gateway retea	Ethernet?Wifi		
Protocol comunica-re	OCPP 1.6J, suporta upgrade la OCPP 2.0.1		
Standard siguranta	EN IEC 61851-1: 2019; IEC 61851-1:2017; EN IEC 61851-21-2:2021; EN IEC 61000-6-1:2019; EN IEC 61000-6-2:2019; EN IEC 61000-6-3:2021; EN IEC 61000-6-4:2019; ETSI EN 300 328 V2.2.2:2019; ETSI EN 300 330 V2.1.1:2017; ETSI EN 301 489-1 V2.2.3:2019; ETSI EN 301 489-3 V2.1.1:2019; ETSI EN 301 489-17 V3.2.4:2020; EN IEC 62311:2020		
Garantie	2 years		
Performanta mediu			
Nivel protectie	IP65		
Altitudine operare	< 2000M		
Loc utilizare	Interior/Exterior		
Temperatura operare	-30 C ~+50C		
Umiditate operare	5%-95%, No condensation		
Presiune atmosferica	80kPa~101kPa		

Configuratie produs

Detalii ambalare			
Dimensiune produs	398*324*120mm	398*324*120mm	398*324*120mm
Greutate produs	10KG	11KG	12KG
Optional Config			
Dynamic load balancing	RS485 meter or local junction box (optinal)		
Contor energie	MID meter		
Gateway retea	4G		

OptionFuncții rance



Tip priza



Tip conector



Type2/GBT Optional



Cablu length customization